

Printed copies are for reference only.




TABLE I

PART NUMBER	NOM. DIA.		A DIA. THEO.		A' DIA. MIN.		C MAX.		D DIA.		E DIA. MAX.		F FLATS		H REF.		J DIA. MAX.		K MAX.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
PLT115-5-(*)	.1635	4,15	.332 .325	8,43 8,25	.296	7,52	.268	6,81	.1645 .1625	4,178 4,128	.1620	4,12	.086 .081	2,18 2,06	.069	1,75	.244	6,20	.246	6,25
PLT115-6-(*)	.1890	4,80	.385 .378	9,78 9,60	.342	8,69	.303	7,70	.1900 .1880	4,826 4,775	.1875	4,77	.104 .099	2,64 2,51	.081	2,06	.300	7,62	.281	7,14
PLT115-8-(*)	.2480	6,30	.507 .499	12,88 12,67	.463	11,76	.354	9,00	.2490 .2470	6,325 6,274	.2465	6,27	.135 .130	3,43 3,30	.107	2,72	.384	9,75	.325	8,26
PLT115-10-(*)	.3105	7,89	.635 .626	16,13 15,90	.577	14,66	.423	10,75	.3115 .3095	7,912 7,861	.3090	7,85	.152 .147	3,86 3,73	.134	3,40	.427	10,85	.390	9,91
PLT115-12-(*)	.3735	9,49	.762 .752	19,35 19,10	.696	17,68	.510	12,96	.3745 .3725	9,512 9,462	.3720	9,45	.185 .180	4,70 4,57	.160	4,06	.516	13,11	.470	11,94

TABLE I (CONT.)

PART NUMBER	M GAGE PROT.		R RAD.		S MAX.		W GAGE DIA.		BREAK-OFF LIMITS		HOLE SIZE		PREVAILING TORQUE MIN.		DOUBLE SHEAR STRENGTH MIN.		TENSILE STRENGTH MIN.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	IN-LBS	Nm	LBS.	N	LBS.	N
PLT115-5-(*)	.0276 .0238	0,701 0,604	.030 .010	0,76 0,25	.012	0,30	.2671 .2667	6,784 6,774	+.020 -.068	+0,51 -1,73	.168 .165	4,27 4,19	1.0	0,113	3355	14900	900	4000
PLT115-6-(*)	.0299 .0259	0,760 0,658	.030 .015	0,76 0,38	.015	0,38	.3147 .3143	7,993 7,983	+.015 -.073	+0,38 -1,85	.193 .190	4,90 4,82	1.5	0,170	4650	20680	1400	6230
PLT115-8-(*)	.0353 .0307	0,897 0,780	.030 .015	0,76 0,38	.015	0,38	.4245 .4241	10,782 10,772	+.010 -.078	+0,25 -1,98	.252 .249	6,40 6,32	2.5	0,282	7770	34560	2100	9340
PLT115-10-(*)	.0409 .0357	1,039 0,907	.040 .020	1,02 0,51	.020	0,51	.5389 .5385	13,688 13,678	+.010 -.083	+0,25 -2,11	.315 .312	8,00 7,92	3.5	0,400	12000	53400	3600	16010
PLT115-12-(*)	.0466 .0407	1,184 1,034	.040 .020	1,02 0,51	.023	0,58	.6532 .6528	16,591 16,581	+.010 -.093	+0,25 -2,36	.378 .375	9,60 9,52	4.0	0,452	19500	86700	5600	24910

(*) SEE TABLE II FOR SECOND DASH NUMBER AND APPROVED CALLOUT.

Fairchild
 CODE IDENT. NO.
92215

MONOGRAM
 CODE IDENT. NO.
98524

U.S. PATENT NO. 3643544, OTHER PATENTS PENDING.

APPROVED DATE
 27 JANUARY 1972
 REV. LETTER AND DATE
"L" 11-19-01 EDN 1173

NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUMES CUSTODY THEREOF AND AGREES: A. THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED. B. WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

TITLE
VISU-LOK, FASTENER, BLIND INTERNALLY THREADED, EXTERNAL SLEEVE ALLOY STEEL 100° FLUSH HEAD, SELF LOCKING FRACTIONAL DIAMETER

STANDARD
PLT 115
SHEET 1 OF 2

TABLE II

SECOND DASH NUMBER	G GRIP (a)		GRIP RANGE \triangle \triangle				L REF.									
			MIN.		MAX.		-5		-6		-8		-10		-12	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
-2	.156	3.96	.094	2.39	.156	3.96	.733	18.62	.853	21.67	-	-	-	-	-	-
-3	.219	5.56	.157	3.99	.219	5.56	.795	20.19	.916	23.27	.944	23.98	-	-	-	-
-4	.281	7.14	.220	5.59	.281	7.14	.858	21.79	.978	24.84	1.006	25.55	1.158	29.41	1.242	31.55
-5	.344	8.74	.282	7.16	.344	8.74	.920	23.37	1.041	26.44	1.069	27.15	1.221	31.01	1.304	33.12
-6	.406	10.31	.345	8.76	.406	10.31	.983	24.97	1.103	28.02	1.131	28.73	1.283	32.59	1.367	34.72
-7	.469	11.91	.407	10.34	.469	11.91	1.045	26.54	1.166	29.62	1.194	30.33	1.346	34.19	1.429	36.30
-8	.531	13.49	.470	11.94	.531	13.49	1.108	28.14	1.228	31.19	1.256	31.90	1.408	35.76	1.492	37.90
-9	.594	15.11	.532	13.51	.594	15.11	1.170	29.72	1.291	32.79	1.319	33.50	1.471	37.36	1.554	39.47
-10	.656	16.66	.595	15.11	.656	16.66	1.233	31.32	1.353	34.37	1.381	35.08	1.533	38.94	1.617	41.07
-11	.719	18.26	.657	16.69	.719	18.26	1.295	32.89	1.416	35.97	1.444	36.68	1.596	40.54	1.679	42.65
-12	.781	19.84	.720	18.29	.781	19.84	1.358	34.49	1.478	37.54	1.506	38.25	1.658	42.11	1.742	44.25
-13	.844	21.44	.782	19.86	.844	21.44	1.420	36.07	1.541	39.14	1.569	39.85	1.721	43.71	1.804	45.82
-14	.906	23.01	.845	21.46	.906	23.01	1.483	37.67	1.603	40.72	1.631	41.43	1.783	45.29	1.867	47.42
-15	.969	24.61	.907	23.04	.969	24.61	1.545	39.24	1.666	42.32	1.694	43.03	1.846	46.89	1.929	49.00
-16	1.031	26.19	.970	24.64	1.031	26.19	1.608	40.84	1.728	43.89	1.756	44.60	1.908	48.46	1.992	50.60
-17	1.094	27.79	1.032	26.21	1.094	27.79	NOT AVAILABLE IN -5 DIAMETER	1.791	45.49	1.819	46.20	1.971	50.06	2.054	52.17	
-18	1.156	29.36	1.095	27.81	1.156	29.36		1.853	47.07	1.881	47.78	2.033	51.46	2.117	53.77	
-19	1.219	30.96	1.157	29.39	1.219	30.96		1.916	48.67	1.944	49.38	2.096	53.24	2.179	55.35	
-20	1.281	32.54	1.220	30.99	1.281	32.54		1.978	50.24	2.006	50.95	2.158	54.81	2.242	56.95	
-21	1.344	34.14	1.282	32.56	1.344	34.14		2.041	51.84	2.069	52.55	2.221	56.41	2.304	58.52	
-22	1.406	35.71	1.345	34.16	1.406	35.71		2.103	53.42	2.131	54.13	2.283	57.99	2.367	60.12	
-23	1.469	37.31	1.407	35.74	1.469	37.31		2.166	55.02	2.194	55.73	2.346	59.59	2.429	61.70	
-24	1.531	38.89	1.470	37.34	1.531	38.89		2.228	56.59	2.256	57.30	2.408	61.16	2.492	63.30	
-25	1.594	40.49	1.532	38.91	1.594	40.49		2.291	58.19	2.319	58.90	2.471	62.76	2.554	64.87	
-26	1.656	42.06	1.595	40.51	1.656	42.06		2.353	59.77	2.381	60.48	2.533	64.34	2.617	66.47	
-27	1.719	43.66	1.657	42.09	1.719	43.66	2.416	61.37	2.444	62.08	2.596	65.94	2.679	68.05		
-28	1.781	45.24	1.720	43.69	1.781	45.24	2.478	62.94	2.506	63.65	2.658	67.51	2.742	69.65		
-29	1.844	46.84	1.782	45.26	1.844	46.84	2.541	64.54	2.569	65.25	2.721	69.11	2.804	71.22		
-30	1.906	48.41	1.845	46.86	1.906	48.41	2.603	66.12	2.631	66.83	2.783	70.69	2.867	72.82		
-31	1.969	50.01	1.907	48.44	1.969	50.01	2.666	67.72	2.694	68.43	2.846	72.29	2.929	74.40		
-32	2.031	51.59	1.970	50.04	2.031	51.59	2.728	69.29	2.756	70.00	2.908	73.86	2.992	76.00		

(a) "G" TOLERANCES: FOR -5 & -6 SIZES $+0.030$ ($+0.77$), -0.010 (-0.25); FOR -8 & -10 SIZES $+0.040$ ($+1.02$), -0.010 (-0.25); FOR -12 SIZE $+0.050$ ($+1.27$), -0.010 (-0.25)

PROCUREMENT SPECIFICATION: ESCBB-2, CLASS I EXCEPT AS NOTED HEREIN.

MATERIAL: NUT & SCREW: ALLOY STEEL: 4130 PER MIL-S-6758, 4140 PER MIL-S-5626, OR 8740 PER MIL-S-6049.

SLEEVE: CORROSION RESISTANT STEEL: 303 OR 304 PER QQ-S-763, AMS 5639, OR AMS 5641.

HEAT TREAT: NUT & SCREW: HEAT TREAT PER MIL-H-6875, APPROXIMATELY 180,000 TO 200,000 PSI (1240 TO 1380 N/mm²) TENSILE (Rc 39-43).

SLEEVE: AS REQUIRED FOR PERFORMANCE

FINISH: NUT & SCREW: CADMIUM PLATE PER QQ-P-416, TYPE II, CLASS 2. CADMIUM PLATE PER NAS 672 IS PERMISSIBLE PROVIDED IT IS FOLLOWED BY A DICHROMATE POST TREATMENT PER QQ-P-416.

SLEEVE: PASSIVATE PER MIL-S-5002. CADMIUM PLATE PER QQ-P-416, TYPE I, CLASS 3.


LUBRICATION: LUBRICANTS LISTED BELOW MAY BE APPLIED TO ANY OR ALL COMPONENTS IF REQUIRED FOR PERFORMANCE:

NUT: W/M CARBO-WAX, PARAFFIN WAX AND/OR CETYL ALCOHOL PER MIL-L-87132.

SCREW & SLEEVE: DRY FILM LUBE MOS₂ PER MIL-L-46010 OR MIL-L-81329, W/M CARBO-WAX, PARAFFIN WAX AND/OR CETYL ALCOHOL PER MIL-L-87132.

GENERAL NOTES:

- OUTSIDE DIAMETER OF HEAD OF SCREW AND OUTSIDE DIAMETER OF SLEEVE SHALL NOT BE GREATER THAN MAXIMUM "E" DIAMETER.
- REMOVE ALL LOOSE OR HANGING BURRS.
- LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120° APART ON THE PERIPHERY OF THE NUT COMPONENT AND APPROXIMATELY .040 ABOVE THE INTERSECTION OF THE NUT NOSE ANGLE AND O.D. (MEAN GRIP OF FASTENER).
- HEAD MARKING ON NUT DEPRESSED .010 IN. (0.26 mm) MAXIMUM.
- STANDARD FINISHES AND LUBRICANTS AS SHOWN ON LEFT. REFER TO SPECIFICATION ESCBB-4 FOR SPECIAL FINISHES AND/OR LUBRICANTS, IF REQUIRED
- CONCENTRICITY OF NUT HEAD CONICAL SURFACE TO "D" DIAMETER SHALL BE WITHIN .005 IN (0.13mm) T.I.R., (EXCEPT OVER INDENTS).
- STANDARD GRIP LENGTHS ARE SHOWN IN TABLE II, SHORTER OR LONGER GRIPS THAN THOSE LISTED MAY BE AVAILABLE AS SPECIALS. ON GRIP LENGTHS SHORTER THAN THOSE LISTED, THE BREAKOFF LIMITS AND PREVAILING TORQUE VALUES SHOWN IN TABLE I DO NOT APPLY.
- DISTORTION OF "D" DIAMETER SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MAXIMUM "D" + .001". FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS (22.23 NEWTONS)
- HALF-GRIP SIZES MAY BE ORDERED BY ADDING (.5) TO THE GRIP DASH NUMBERS EXAMPLE: PLT115-6-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 16THS (.281" = 7.14mm) THE GRIP RANGE FOR THESE HALF GRIP SIZES WILL BE NOMINAL GRIP +.031/-0.030 (+0.79/-0.76 mm) THE BASIC "G" DIMENSION WILL BE MAXIMUM GRIP +.031 (+0.79mm) AND THE OVERALL SCREW LENGTH "L" DIMENSION MAY VARY AT THE MANUFACTURER'S OPTION
- DIMENSIONS "A", "A'" AND "H" ARE FOR ENGINEERING REFERENCE PURPOSES ONLY AND ARE NOT TO BE USED FOR INSPECTION PURPOSES. THESE DIMENSIONS ARE THEORETICAL VALUES DERIVED FROM "D", "S", "V", "W" AND HEAD ANGLE DIMENSIONS.
- DIMENSIONS ARE EXCLUSIVE OF LUBRICATION.
- PLT115-5-(*) IS EQUIVALENT TO PLT110-5-(*)
 PLT115-10-(*) IS EQUIVALENT TO PLT110-10-(*)
 PLT115-12-(*) IS EQUIVALENT TO PLT110-12-(*)



Fairchild
 CODE IDENT. NO.
92215

MONOGRAM
 CODE IDENT. NO.
98524

U.S. PATENT NO. 3643544, OTHER PATENTS PENDING.

APPROVED DATE
 27 JANUARY 1972

REV. LETTER AND DATE
"L" 11-19-01 EDN 1173

NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUMES CUSTODY THEREOF AND AGREES: A. THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED. B. WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

TITLE
VISU-LOK, FASTENER, BLIND INTERNALLY THREADED, EXTERNAL SLEEVE ALLOY STEEL 100° FLUSH HEAD, SELF LOCKING FRACTIONAL DIAMETER

STANDARD
PLT 115
SHEET 2 OF 2