


Printed copies are for reference only.



HEAD MARKINGS DEPRESSED .010 INCH (0,254 mm MAX.) (POSITION OPTIONAL)
* DRIVE-NUT NOT SHOWN FOR CLARITY OF HEAD MARKINGS.

TABLE I

PART NUMBER	NOM. DIA.		A DIA. THEO.		A' DIA. MIN.		C MAX.		D DIA.		F FLATS		H REF.		J DIA. MAX.		K REF.		R RAD.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
PLT 5112-6-()	.2290	5,817	.385 .378	9,78 9,60	.342	8,69	.360	9,14	.2300 .2280	5,84 5,79	.104 .099	2,64 2,52	.063	1,60	.315	8,00	.334	8,48	.030 .015	0,76 0,38
PLT 5112-8-()	.2900	7,366	.507 .499	12,88 12,67	.463	11,76	.404	10,26	.2910 .2890	7,39 7,34	.135 .130	3,43 3,30	.087	2,21	.401	10,19	.375	9,52	.030 .015	0,76 0,38
PLT 5112-10-()	.3415	8,674	.635 .626	16,13 15,90	.577	14,66	.493	12,52	.3425 .3405	8,70 8,65	.152 .147	3,86 3,73	.118	3,00	.442	11,23	.460	11,68	.040 .020	1,02 0,51
PLT 5112-12-()	.4045	10,273	.762 .752	19,35 19,10	.696	17,68	.583	14,80	.4055 .4035	10,30 10,25	.185 .180	4,70 4,57	.144	3,66	.531	13,49	.543	13,79	.040 .020	1,02 0,51

TABLE I (CONT.)

PART NUMBER	S MAX.		V GAGE PROT.		W GAGE DIA.		BREAK-OFF LIMITS		MINIMUM AVAILABLE GRIP LENGTH (TABLE II)	HOLE SIZE		PREVAILING TORQUE MIN.		DOUBLE SHEAR STRENGTH MIN.		TENSILE STRENGTH MIN.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm		INCH	mm	IN-LB	Nm	LBS.	N	LBS.	N
PLT 5112-6-()	.015	0,38	.0299 .0259	0,759 0,658	.3147 .3143	7,993 7,983	+.015 -.073	+0,38 -1,85	-2	.233 .230	5,92 5,84	1.5	0,170	5240	23300	1400	6230
PLT 5112-8-()	.015	0,38	.0353 .0307	0,897 0,780	.4245 .4241	10,782 10,772	+.010 -.078	+0,25 -1,98	-3	.294 .291	7,47 7,39	2.5	0,282	9000	40000	2100	9340
PLT 5112-10-()	.020	0,51	.0409 .0357	1,039 0,907	.5389 .5385	13,688 13,678	+.010 -.083	+0,25 -2,11	-4	.346 .343	8,79 8,71	3.5	0,400	12000	53400	3600	16010
PLT 5112-12-()	.023	0,58	.0466 .0407	1,184 1,034	.6532 .6528	16,591 16,581	+.010 -.093	+0,25 -2,36	-4	.409 .406	10,39 10,31	4.0	0,452	19500	86700	5600	24910

VOI-SHAN
CODE IDENT. NO.
92215

APPROVED DATE
11-27-85 ECN 4345

REV. LETTER AND DATE
"C" 8-1-91 ECN 6816

U.S. PATENT NO. 3643544, 4747202, AND 4967463
EUROPEAN PATENT NO. 0152531 AND 0216980

MONOGRAM
CODE IDENT. NO.
98524

STANDARD
PLT 5112
SHEET 1 OF 2

TITLE
VISU-LOK® II FASTENER, BLIND
100° FLUSH TENSION HEAD 1/32 O/S DIAMETER
ALLOY STEEL

APPLICABLE SPECIFICATIONS:

PROCUREMENT SPECIFICATION = PLT 5000 CLASS I, TYPE I
PART NUMBER ASSIGNMENT = PLT 5001
INSTALLATION AND REMOVAL = PLT 5002
SPECIAL LUBE AND FINISH = PLT 5003


MATERIAL: NUT & SCREW: ALLOY STEEL; 4130 PER MIL-S-6758, 4140 PER MIL-S-5626 OR 8740 PER MIL-S-6049
SLEEVE: CORROSION RESISTANT STEEL; 303 PER AMS 5639 OR 304 PER AMS 5641
DRIVE NUT: MILD STEEL

HEAT TREAT: NUT & SCREW: HEAT TREAT PER MIL-H-6875 TO RC 39-43
SLEEVE: AS REQUIRED FOR PERFORMANCE
DRIVE NUT: AS REQUIRED FOR PERFORMANCE

FINISH: NUT & SCREW: CADMIUM PLATE PER QQ-P-416 TYPE II, CL. 2
CADMIUM PLATE PER NAS 672 IS PERMISSIBLE PROVIDED IT IS FOLLOWED BY A DICHROMATE POST TREATMENT PER QQ-P-416
SLEEVE: PASSIVATED PER MIL-S-5002 CADMIUM PLATED PER QQ-P-416 TYPE I, CL. 3
DRIVE NUT: CORROSION RESISTANT COATING. COLOR GOLD

LUBRICATION: SOLID DRY FILM LUBRICANT PER THE CHEMICAL REQUIREMENTS OF MIL-L-8937, OR EVERLUBE 812 PER MIL-L-81329, PARAFFIN WAX OR CETYL ALCOHOL PER MIL-L-87132 MAY BE APPLIED TO ANY OR ALL COMPONENTS AS REQUIRED FOR PERFORMANCE, (SEE PLT 5003 FOR SPECIAL LUBRICANTS AND FINISHES)

PART CODE & EXAMPLE:



GENERAL NOTES:

- ① LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120° APART ON THE PERIPHERY OF THE NUT COMPONENT
- ② HALF GRIP SIZES MAY BE ORDERED BY ADDING .5 TO THE GRIP DASH NUMBER
EXAMPLE: PLT 5112-6-4.5 HAS A NOMINAL GRIP LENGTH OF 4-1/2 16THS (.281" = 7.14 mm) AND A GRIP RANGE OF .250" THRU .312" (6.35 mm THRU 7.92 mm)
- ③ DISTORTION OF "D" DIAMETER SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MINIMUM RECOMMENDED HOLE SIZE. FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS (22.23 NEWTONS)
- ④ SECOND DASH NUMBER (GRIP RANGE) -17 THROUGH -32 NOT AVAILABLE IN -5 DIAMETER

TABLE II

2ND DASH NO. ④	GRIP RANGE ②			
	MIN. GRIP		MAX. GRIP	
	INCH	mm	INCH	mm
-2	.094	2,39	.156	3,96
-3	.157	3,99	.219	5,56
-4	.220	5,59	.281	7,14
-5	.282	7,16	.344	8,74
-6	.345	8,76	.406	10,31
-7	.407	10,34	.469	11,91
-8	.470	11,94	.531	13,49
-9	.532	13,51	.594	15,09
-10	.595	15,11	.656	16,66
-11	.657	16,69	.719	18,26
-12	.720	18,29	.781	19,84
-13	.782	19,86	.844	21,44
-14	.845	21,46	.906	23,01
-15	.907	23,04	.969	24,61
-16	.970	24,64	1,031	26,19
-17	1,032	26,21	1,094	27,79
-18	1,095	27,81	1,156	29,36
-19	1,157	29,38	1,219	30,97
-20	1,220	30,98	1,281	32,54
-21	1,282	32,55	1,344	34,14
-22	1,345	34,15	1,406	35,72
-23	1,407	35,73	1,469	37,32
-24	1,470	37,33	1,531	38,89
-25	1,532	38,90	1,594	40,49
-26	1,595	40,50	1,656	42,07
-27	1,657	42,08	1,719	43,67
-28	1,720	43,68	1,781	45,24
-29	1,782	45,25	1,844	46,84
-30	1,845	46,85	1,906	48,42
-31	1,907	48,43	1,969	50,02
-32	1,970	50,03	2,031	51,59

VOI-SHAN
CODE IDENT. NO.
92215

U.S. PATENT NO. 3643544, 4,747,202, AND 4967463
EUROPEAN PATENT NO. 0152531 AND 0216980

MONOGRAM
CODE IDENT. NO.
98524

APPROVED DATE
11-27-85 ECN 4345

REV. LETTER AND DATE
"C" 8-1-91 ECN 6816

TITLE
VISU-LOK® II FASTENER, BLIND
100° FLUSH TENSION HEAD 1/32 O/S DIAMETER
ALLOY STEEL

STANDARD
PLT 5112
SHEET 2 OF 2