



PART NUMBER	NOM DIA.		A THEO DIA.		A' DIA. MIN.		C MAX.		D DIA.		F FLATS		H REF.		J DIA. MAX.		K MAX.		L1 REF.		L3 REF.	
	INCH	mm	INCH	MM	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
PLT5471-05-(-)	.1790	4.55	.2612 .2564	6.63 6.51	.241	6.12	.315	8.00	.1800 .1780	4.572 4.521	.086 .081	2.18 2.06	.033	0.84	.244	6.20	.300	7.62	.385	9.78	.626	15.90
PLT5471-06-(-)	.2140	5.44	.3016 .2966	7.66 7.53	.270	6.86	.350	8.89	.2150 .2130	5.461 5.410	.104 .099	2.64 2.52	.036	0.91	.300	7.62	.333	8.46	.431	10.95	.610	15.49
PLT5471-08-(-)	.2750	6.98	.3948 .3898	10.03 9.90	.363	9.22	.385	9.78	.2760 .2740	7.010 6.960	.135 .130	3.43 3.30	.049	1.24	.384	9.75	.366	9.30	.477	12.12	.706	17.93
PLT5471-10-(-)	.3260	8.28	.4739 .4689	12.04 11.91	.442	11.23	.470	11.94	.3270 .3250	8.306 8.255	.152 .147	3.86 3.73	.061	1.55	.427	10.85	.447	11.35	.595	15.11	.938	23.83
PLT5471-12-(-)	.3890	9.88	.5604 .5554	14.23 14.11	.529	13.44	.555	14.10	.3900 .3880	9.906 9.855	.185 .180	4.70 4.57	.071	1.80	.516	13.11	.527	13.39	.704	17.88	1.013	25.73

PART NUMBER	R RAD.		S MAX.		V GAGE DIA.		W GAGE DIA.		BREAK-OFF LIMITS		MINIMUM AVAILABLE GRIP LENGTH	HOLE SIZE		PREVAILING TORQUE MIN.		DOUBLE SHEAR STRENGTH MIN.		TENSILE STRENGTH MIN.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm		INCH	mm	IN-LB	Nm	LBS.	N	LBS.	N
PLT5471-05-(-)	.030 .010	0.76 0.25	.010	0.25	.0178 .0153	0.452 0.389	.2195 .2193	5.575 5.570	+0.088 -0.000	+2.23 -0.00	-02	.183 .181	4.65 4.60	1.0	0.113	3800	16900	750	3336
PLT5471-06-(-)	.030 .015	0.76 0.38	.015	0.38	.0246 .0218	0.625 0.554	.2440 .2438	6.198 6.193	+0.088 -0.000	+2.23 -0.00	-02	.218 .216	5.54 5.49	1.5	0.170	5400	24020	1250	5560
PLT5471-08-(-)	.030 .015	0.76 0.38	.015	0.38	.0271 .0242	0.688 0.615	.3314 .3312	8.418 8.413	+0.098 -0.000	+2.49 -0.00	-03	.279 .277	7.09 7.04	2.5	0.282	8900	40000	1900	8450
PLT5471-10-(-)	.040 .020	1.02 0.51	.015	0.38	.0296 .0266	0.752 0.676	.4047 .4045	10.279 10.274	+1.103 -0.000	+2.62 -0.00	-03	.330 .328	8.38 8.33	3.5	0.400	12500	55600	3250	14457
PLT5471-12-(-)	.040 .020	1.02 0.51	.015	0.38	.0321 .0290	0.815 0.737	.4854 .4852	12.329 12.324	+1.103 -0.000	+2.62 -0.00	-04	.393 .391	9.98 9.93	4.0	0.452	17800	79180	5050	22464

MONOGRAM AEROSPACE FASTENERS
 a TriMas company
 3423 SOUTH GARFIELD AVENUE
 COMMERCE, CALIFORNIA 90040
 (323) 722-4760 FAX (323) 727-1029

TITLE:
**VISU-LOK®II, FASTENER, BLIND
 100° REDUCED FLUSH SHEAR HEAD
 1/64 OVERSIZE DIAMETER
 TITANIUM ALLOY**

DRAWING NO:
PLT5471(-)(-)(-)

DRAWN BY: G.MARTINEZ
 DRAWN DATE: 08-21-13

APPROVED BY: _____
 CHECKED DATE: _____

PROPRIETARY AND CONFIDENTIAL:
 NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
 A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
 B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa
 CAGE CODE: 5M902

MONOGRAM
 CAGE CODE: 98524

ECN NO: 14-0815
 ECN DATE: 11/22/14

REV: L
 SHEET 1 OF 2



4 2ND DASH NO.	GRIP RANGE 2			
	GRIP MIN.		GRIP MAX.	
	INCH	mm	INCH	mm
-	-	-	-	-
-02	.094	2,39	.156	3,96
-03	.157	3,99	.219	5,56
-04	.220	5,59	.281	7,14
-05	.282	7,16	.344	8,74
-06	.345	8,76	.406	10,31
-07	.407	10,34	.469	11,91
-08	.470	11,94	.531	13,49
-09	.532	13,51	.594	15,09
-10	.595	15,11	.656	16,66
-11	.657	16,69	.719	18,26
-12	.720	18,29	.781	19,84
-13	.782	19,86	.844	21,44
-14	.845	21,46	.906	23,01
-15	.907	23,04	.969	24,61
-16	.970	24,64	1,031	26,19

4 2ND DASH NO.	GRIP RANGE 2			
	GRIP MIN.		GRIP MIN.	
	INCH	mm	INCH	mm
-17	1,032	26,21	1,094	27,79
-18	1,095	27,81	1,156	29,36
-19	1,157	29,38	1,219	30,97
-20	1,220	30,98	1,281	32,54
-21	1,282	32,55	1,344	34,14
-22	1,345	34,15	1,406	35,72
-23	1,407	35,73	1,469	37,32
-24	1,470	37,33	1,531	38,89
-25	1,532	38,90	1,594	40,49
-26	1,595	40,50	1,656	42,07
-27	1,657	42,08	1,719	43,67
-28	1,720	43,68	1,781	45,24
-29	1,782	45,25	1,844	46,84
-30	1,845	46,85	1,906	48,42
-31	1,907	48,43	1,969	50,02
-32	1,970	50,03	2,031	51,59



PROCUREMENT SPEC:

PROCUREMENT SPECIFICATION = PLT5000, CLASS 5, TYPE III
 PART NUMBER ASSIGNMENT = PLT5001
 INSTALLATION AND REMOVAL = PLT5002
 SPECIAL LUBE AND FINISH = PLT5003

MATERIAL: " - " NUT & SCREW: 6AL-4V TITANIUM PER AMS4928 OR AMS4967.
 SLEEVE: CORROSION RESISTANT STEEL.
 DRIVE NUT: MILD STEEL.

HEAT TREAT: " - " NUT & SCREW: HEAT TREAT TO 95 KSI, FSU.
 DRIVE NUT & SLEEVE: AS REQUIRED FOR PERFORMANCE.

FINISH: " - " NUT & SCREW: NONE.
 SLEEVE: PASSIVATE PER AMS2700.
 DRIVE NUT: CORROSION RESISTANT COATING, COLOR GRAY.

LUBRICANT: SOLID DRY FILM LUBE PER THE CHEMICAL REQUIREMENTS OF AS5272 TYPE I OR EVERLUBE 812 PER MIL-PRF-81329, PARAFFIN WAX OR CETYL ALCOHOL PER AS87132 MAY BE APPLIED TO ANY OR ALL COMPONENTS AS REQUIRED FOR PERFORMANCE. (SEE PLT 5003 FOR SPECIAL LUBRICANTS AND FINISHES).

PART CODE & EXAMPLE: PLT5471 () - 08 - 04

GENERAL NOTES:

1. LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120° APART ON THE PERIPHERY OF THE NUT COMPONENT.
2. HALF-GRIP SIZES MAY BE ORDERED BY ADDING (.5) TO THE GRIP DASH NUMBERS.
 EXAMPLE: PLT5471-06-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 SIXTEENTHS = 0.281" (7,14mm) AND A GRIP RANGE OF .250" THRU .312" (6,35mm THRU 7,92mm).
3. DISTORTION OF "D" DIAMETER SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MINIMUM RECOMMENDED HOLE SIZE. FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS (22.23 NEWTONS).
4. SECOND DASH NUMBER (GRIP RANGE) -17 THROUGH -32 NOT AVAILABLE IN -05 DIAMETER.
5. "J" AND "K" ARE FOR DESIGN PURPOSES ONLY, NOT FOR INSPECTION IN ACTUAL APPLICATION.
6. HEAD MARKINGS DEPRESSED .010" (0,254mm MAX.), POSITION OPTIONAL.



TITLE:
 VISU-LOK®II, FASTENER, BLIND
 100° REDUCED FLUSH SHEAR HEAD
 1/64 OVERSIZE DIAMETER
 TITANIUM ALLOY

DRAWING NO: PLT5471 () - () - ()	
DRAWN BY: G.MARTINEZ	DRAWN DATE: 08-21-13
APPROVED BY:	CHECKED DATE:

PROPRIETARY AND CONFIDENTIAL: NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
 A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
 B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa
 CAGE CODE:
 5M902

MONOGRAM
 CAGE CODE:
 98524

ECN NO:
 14-0815
 ECN DATE:
 11/22/14

REV:
 L
 SHEET 2 OF 2